



IN THE CLAIMS

This listing of the claim will replace all prior versions and listings of claim in the present application.

Listing of Claims

1. (currently amended) A server system comprising a plurality of servers that can be each operated as a primary system and a standby system by system switching, and a shared disk unit for storing data accessed by said plurality of servers, wherein:

wherein each of said plurality of servers comprises:

an application means;

a driver means that acquires information on a configuration inside said shared disk unit after starting of said system; and, based on said configuration information, sets said shared disk unit in an active state in which an access request to said shared disk unit can be sent; and, when the driver means receives an access request to said shared disk unit, sends said access request to said shared disk unit; and

an access control means that judges whether an access request issued by said application means should be sent, based on a management table indicating inhibited types of access requests for each access destination; and sends said access request to said driver means when said access request is not inhibited for an access destination of said access request;

wherein a server operating as the primary system and a server operating as the standby system are each set to an active state during normal

operation and access requests of the standby system are inhibited based on the management table.

2. (currently amended) The server system according to Claim 1, wherein: when a fault occurs in a server operating as the primary system, then the access control means of said server registers in said management table such that an access request of said application means to any access destination is inhibited.

3. (currently amended) The server system according to Claim 1, wherein: said server system further comprises a console for sending said plurality of servers a system switching command inputted by an operator; and when a server operates as the primary system and the access control means of said server receives said system switching command, then, said access control means registers in said management table such that an access request of said application means to any access destination is inhibited.

4. (currently amended) The server system according to Claim 1 or claims 2 or 3, wherein: said access control means registers in said management table such that, as said access request, at least write is inhibited.

5. (currently amended) The server system according to Claim 1,
wherein: said management table indicates an inhibited read and/or write
access request for each access destination; and
wherein said access control means judges, based on said
management table, whether a read or write access request issued by said
application means should be sent, and sends the read or write access request
to said driver means when said access request is directed to an access
destination for which the read or write access request is not inhibited.

6. (currently amended) The server system according to Claim 1,
wherein: said management table indicates an inhibited file open and/or file
close access request for each access destination; and
wherein said access control means judges, based on said
management table, whether a file open or file close access request issued by
said application means should be sent, and sends the file open or file close
access request to said driver means when said access request is directed to
an access destination for which the file open or file close access request is
not inhibited.

7. (currently amended) The server system according to Claim 1,
wherein: said server system further comprises a console for sending said
plurality of servers a command for registering, deleting or changing inhibited
access requests for each access destination, with said command being
inputted by an operator; and

when said access control means receives said command, then, according to said command, said access control means registers, deletes or changes an identifier specifying an access destination and types of access requests inhibited for said access destination, in said management table.

8. (original) The server system according to Claim 1, further comprising:

a console for sending each of said plurality of servers a command that is inputted by an operator and that requests contents of the management table, and for outputting the contents of the management table received from the server in question.

9. (currently amended) A server that can operate as a primary system and a standby system by system switching, comprising:

an application means;
a driver means that: acquires, after starting of said server, information on a configuration inside a shared disk unit whose data are shared by a plurality of servers; and, based on said configuration information, sets said shared disk unit in an active state in which an access request to said shared disk unit can be sent; and, when the driver means receives an access request to said shared disk unit, sends said access request to said shared disk unit; and

an access control means that: judges whether an access request issued by said application means should be sent, based on a management table indicating inhibited types of access requests for each access

destination; and sends said access request to said driver means when said access request is not inhibited for an access destination of said access request.

wherein the server operating as the primary system and as the standby system are each set to an active state during normal operation and access requests of the standby system are inhibited based on the management table.

10. (currently amended) A computer readable storage medium storing a program for making a server operate as a primary system and a standby system by system switching, with said server being provided with a driver means that receives an access request to a shared disk unit whose data are shared by a plurality of servers and that, on receiving said access request, sends said access request to said shared disk unit, wherein: said program makes said server execute:

processing of acquiring, after starting of said server, information on a configuration inside said shared disk unit, and of instructing said driver means based on said configuration information to set said shared disk unit in an active state in which an access request to said shared disk unit can be sent, and

processing of judging whether an access request issued by execution of another application program should be sent, based on a management table indicating inhibited types of access requests for each access destination, and of sending said access request to said driver means

when said access request is not inhibited for an access destination of said access request.

wherein a server operating as the primary system and a server operating as the standby system are each set to an active state during normal operation and access requests of the standby system are inhibited based on the management table.

11. (currently amended) A computer readable storage medium storing a program for making a server operate as a primary system and a standby system by system switching, wherein: said program makes said server execute:

processing of acquiring, after starting of said server, information on a configuration inside a shared disk whose data are shared by a plurality of servers, and of setting, based on said configuration information, said shared disk unit in an active state in which an access request to said shared disk unit can be sent; and

processing of judging whether an access request issued by execution of another application program should be sent, based on a management table indicating inhibited types of access requests for each access destination, and of sending said access request to said shared disk unit when said access request is not inhibited for an access destination of said access request.

wherein a server operating as the primary system and a server operating as the standby system are each set to an active state during normal

operation and access requests of the standby system are inhibited based on the management table.

12. (currently amended) The storage medium according to Claim 11, wherein: said program further functions as an OS in said server.

13. (currently amended) A method of access control in a server that can operate as a primary system and a standby system by system switching, comprising:

processing of acquiring, after starting of said server, information on a configuration inside a shared disk whose data are shared by a plurality of servers, and of setting, based on said configuration information, said shared disk unit in an active state in which an access request to said shared disk unit can be sent; and

processing of judging whether an access request issued by execution of another application program should be sent, based on a management table indicating inhibited types of access requests for each access destination, and of sending said access request to said shared disk unit when said access request is not inhibited for an access destination of said access request,

wherein a server operating as the primary system and a server operating as the standby system are each set to an active state during normal operation and access requests of the standby system are inhibited based on the management table.

14. (new) A method of access control in a server system having a server operated as a primary system, a server operated as a standby system, and a shared disk storing data accessed by both servers, the method comprising:

a process of setting an active state in which, after starting the servers, information on a configuration inside said shared disk unit can be acquired, and based on said configuration information, an access request to said shared disk unit can be sent;

a process of sending an access request issued by the server operated as the primary system, to the shared disk unit, based on a management table indicating inhibited access requests for each access destination, and of blocking an access request issued by the server operated as the standby system; and

a process of changing the management table, when a fault occurs in the server operated as the primary system, blocking the access request issued by the server operated as the primary system, and sending the access request issued by the server operated as the standby system, to the shared disk unit,

wherein a server operating as the primary system and a server operating as the standby system are each set to an active state during normal operation and access requests of the standby system are inhibited based on the management table.